



the key to a better tomorrow...



Coolers, Oven, Lens, Cleaners & NDT Products



Crack Check

Pro Cool II VANE PUMP



Specifications

- Factory set at 50 psi adjustable to 80 psi
- 3 gallon reservoir
- 115 or 230 vac / single phase - 50/60 hz
- 12,000 BTU
- Dimensions: 18”L x 14”W x 9”H
- 5/8 LH Std. Inert Gas fittings - 1/4”FPT
- 8 foot power cord
- Visible water level through tank
- Thermal overload
- Net weight: 37 lbs / 17 kg
- Foam packed for UPS shipment

Pro Cool II VANE PUMP (PCIIV-115)

- 1.7 gpm at 50 psi
- Rebuilt Pump with New Warranty (Part no. P1103).

PCIIV-115



VH1000V-115

The Dynaflux upright water cooler operates either in a vertical position for welding carts for space savings, or in a horizontal position for conventional applications. The new extended life pump features a direct drive power system reducing maintenance and increasing performance.

Characteristics

- Plastic Water Tank eliminates coolant contamination due to electrolyte or chemical reactions.
- All units are plumbed with copper tubing and reinforced hose.
- New extended life pump features a direct drive power system reducing maintenance and increasing performance.
- No external plumbing is required because of closed loop water system with pressure relief valves as standard equipment.
- Self-Priming Pump

15 Month Limited Warranty

Defense Anti-Freeze and Pump Lubricant(Weldmark® part# WM929) provides year round protection for Dynaflux water coolers and other closed loop water recirculators. NOTE: Use of automotive anti-freeze compounds voids warranty and shortens pump life.



OV50 - Rod Oven

50 lb capacity for 12”, 14” and 18”
(electrodes with adjustable thermostat)

Part#	Description	Std. Pkg.
315KIT-S	Crack Check Kit, NDT Standard--(Contains 1 can of DNF315-16, PHF315-16 and 2 cans of CNF315-16).....	1 Kit
CF315-16	Cleaner, NDT Nuclear, 15.2 oz 12/case	1 Case
CNF315-16	Cleaner, NDT Standard, 15.2 oz 12/case.....	1 Case
CR365-16	Cleaner, Super Solv. 15.1 oz (12/case)	1 Case
CR370-16	Cutting Fluid, All Metal Heavy Duty 12 oz (12/case).....	1 Case
CR601-6	Tungsten Holder, 6 per case	1 Case
DF315-16	Developer, NDT Nuclear, 14.2 oz 12/case	1 Case
DF927-4x1	Coolant/Anti-Freeze “Defense”, 4 gal./cs (non-dilutable)	1 Case
DNF315-16	Developer, NDT Standard, 14.2oz 12/case.....	1 Case
HTR120-3A	Replacement Boots, Spoon Applicator - 6 per pkg.	1 Pkg
HTR120-4X1	Heat Tint Solution 4 gal/case.....	1 Case
HTR120-6	Heat Tint Solution 16 oz (6/case)	1 Case
OV50	Rod Oven, 50lb. capacity 115VAC.....	1
PCIIV-115	Water Recirculator, 3 gal. 115VAC Bench Type	1
PHF315-16	Penetrant, NDT Standard/Nuclear, 9.4oz 12/case	1 Case
UVT01	Lens Safety/Cover “Tufcote”, 2x4 -1/4” clear	100
UVT02	Lens Safety/Cover “Tufcote”, 4 -1/2” x 5 - 1/4” clear	50
VH1000V-115	Water Recirculator, 2 gal. 115VAC Vertical Bench Type	1